



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Bayco Products, Inc.	Manufacturer:	Longkou Dongli Wire and Cable Co., Ltd.
Address:	640 S. Sanden Blvd Wylie, TX 75098	Address:	413 Beihuan Road, Huangcheng, Longkou Shandong P.R.
Country:	USA	Country:	China
Contact:	Mr. Jeff Rooker	Contact:	Daniel
Phone:	(469) 326-9400	Phone:	0535-3126900 / 15306382326
FAX:	(214) 503-1729	FAX:	0535-8526169
Email:	jrooker@baycoproducts.com	Email:	daniel@dongfang-china.com
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Dallas, TX		
Control Number:	<u>4003544</u>	Authorized by:	<u><i>Patricia Starr</i></u> William T. Starr, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
165 Main Street, Cortland, NY 13045
Telephone 800-345-3851 or 607-753-6711 Fax 607-756-6699



AUTHORIZATION TO MARK

Standard(s):	Explosive atmospheres – Part 0: Equipment – General requirements (ANSI/UL 60079-0-2009, 5th Ed., Issued 10/21/2009); Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i" (ANSI/UL 60079-11-2009, 5th Ed., Issued 09/30/2009); Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations (ANSI/UL 913-2011, 7th Ed., Issued 07/31/2006, Rev. 09/23/11); Electrical apparatus for explosive gas atmospheres – Part 0: General requirements (CAN/CSA-C22.2 No. 60079-0:07, 1st Ed., Issued March 2007); Electrical apparatus for explosive gas atmospheres – Part 11: Intrinsic safety "i" (CAN/CSA-E60079-11:02, 2nd Ed., Issued March 2002, Reaffirmed 2011); Intrinsically safe and non-incendive equipment or use in hazardous locations (CAN/CSA-C22.2 No. 157-92, 3rd Ed., Issued June 1992, with Update No. 2, June 2003, Reaffirmed 2012); Enclosures for Use in Class H Groups E, F, and G Hazardous Locations (CSA C22.2 No. 25-1966, Issued September 1966, Reaffirmed 2004)
Product:	Portable LED Intrinsically Safe Headlamp For Use In: Class I, Division 1, Groups A, B, C & D; Class II, Division 1, Groups E, F & G; Class III; Class I, Zone 0; and Class II, Zone 20 Hazardous (Classified) Locations Protection Method: AEx ia IIC T3 Ga and Ex ia IIC T3 Ga; AEx ia IIIC T165°C Da Temperature Code: T3 Ambient Temperature Range: -20 °C (-4 °F) to +40 °C (+104 °F)
Brand Name:	Nightstick
Models:	XPP-5456, XPP-5458