



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant: Bayco Products, Inc.

Address: 640 South Sanden Boulevard
Wylie, TX 75098

Country: USA

Contact: Jim Conner

Phone: 469-326-9452

FAX: 469-326-9402

Email: jconner@baycoproducts.com

Manufacturer: Far East Lighting Co., Ltd.

Address: Sanbei Cixi Ningbo
315331

Country: China

Contact: Judy Huang

Phone: 0086-574-63739017

FAX: 0086-574-63739015

Email: fe2@fareastlamp.com

Party Authorized To Apply Mark: Same as Manufacturer
Report Issuing Office: Dallas, TX

Control Number: 4002026

Authorized by: _____
for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672



AUTHORIZATION TO MARK

	<p>Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II & III, Division 1, Hazardous (Classified) Locations (ANSI/UL 913-2011, Seventh Ed., Issued July 31, 2006, Revised September 23, 2011);</p> <p>Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations (CAN/CSA-C22.2 No. 157-92 (R2012), Third Edition, Issued June 1992, with Update No. 2, June 2003);</p> <p>Enclosures for Use in Class II Groups E, F & G Hazardous Locations General Instruction No 1 (CSA C22.2 No. 25-1966 (R2009), Issued September 1966);</p>
Standard(s):	<p>Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i" (ANSI/UL 60079-11-2011, Fifth Ed., Issued September 30, 2009, Revised May 5, 2011);</p> <p>Explosive atmospheres – Part 0: Equipment – General requirements (ANSI/UL 60079-0-2009, Fifth Ed., Issued October 21, 2009, Revised December 8, 2009);</p> <p>Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i" (CAN/CSA-C22.2 No. 60079-11:11, First Ed. , Issued December 2011);</p> <p>Explosive atmospheres — Part 0: Equipment — General requirements (CAN/CSA-C22.2 No. 60079-0:11, Second Ed., Issued December 2011)</p>
	<p>Portable LED Flashlight and/or Floodlight</p>
Product:	<p>For Use In: Class I, Division 1, Groups A, B, C & D; Class II, Division 1, Groups E, F & G; Class III; Class I, Zone 0; Hazardous (Classified) Locations Protection Method: AEx ia IIC T3 Ga and Ex ia IIC T3 Ga; Temperature Code: T3 Ambient Temperature Range: -20 °C (-4 °F) to +40 °C (+104 °F)</p>
Brand Name:	Nightstick
Models:	XPP-5420 and XPP-5422. May be followed by B or G. XPP 5422 may be followed by GM



AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Bayco Products, Inc.	Manufacturer:	Longkou Dongli Wire and Cable Co., Ltd.
Address:	640 South Sanden Boulevard Wylie, TX 75098	Address:	413 Beihuan Road, Huangcheng, Longkou
Country:	USA	Country:	China
Contact:	Jim Conner	Contact:	Daniel
Phone:	469-326-9452	Phone:	0535-3126900 / 15306382326
FAX:	469-326-9402	FAX:	0535-8526169
Email:	jconner@baycoproducts.com	Email:	daniel@dongfang-china.com

Party Authorized To Apply Mark: Same as Manufacturer
Report Issuing Office: Dallas, TX

Control Number: 4003544

Authorized by: _____
for Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672



AUTHORIZATION TO MARK

	<p>Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II & III, Division 1, Hazardous (Classified) Locations (ANSI/UL 913-2011, Seventh Ed., Issued July 31, 2006, Revised September 23, 2011);</p> <p>Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations (CAN/CSA-C22.2 No. 157-92 (R2012), Third Edition, Issued June 1992, with Update No. 2, June 2003);</p> <p>Enclosures for Use in Class II Groups E, F & G Hazardous Locations General Instruction No 1 (CSA C22.2 No. 25-1966 (R2009), Issued September 1966);</p>
Standard(s):	<p>Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i" (ANSI/UL 60079-11-2011, Fifth Ed., Issued September 30, 2009, Revised May 5, 2011);</p> <p>Explosive atmospheres – Part 0: Equipment – General requirements (ANSI/UL 60079-0-2009, Fifth Ed., Issued October 21, 2009, Revised December 8, 2009);</p> <p>Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i" (CAN/CSA-C22.2 No. 60079-11:11, First Ed. , Issued December 2011);</p> <p>Explosive atmospheres — Part 0: Equipment — General requirements (CAN/CSA-C22.2 No. 60079-0:11, Second Ed., Issued December 2011)</p>
Product:	<p>Portable LED Flashlight and/or Floodlight</p> <p>For Use In: Class I, Division 1, Groups A, B, C & D; Class II, Division 1, Groups E, F & G; Class III; Class I, Zone 0; Hazardous (Classified) Locations</p> <p>Protection Method: AEx ia IIC T3 Ga and Ex ia IIC T3 Ga;</p> <p>Temperature Code: T3</p> <p>Ambient Temperature Range: -20 °C (-4 °F) to +40 °C (+104 °F)</p>
Brand Name:	Nightstick
Models:	XPP-5420 and XPP-5422. May be followed by B or G. XPP 5422 may be followed by GM